

Inverter Compatibility with Ultra High-Power Modules

A Technical Overview

Presented by Omar al-Darwish, Applications Engineer SMA MEA



Disclaimer



IMPORTANT LEGAL NOTICE

This presentation does not constitute or form part of, and should not be construed as, an offer or invitation to subscribe for, underwrite or otherwise acquire, any securities of SMA Solar Technology AG (the "Company") or any present or future subsidiary of the Company (together with the Company, the "SMA Group") nor should it or any part of it form the basis of, or be relied upon in connection with, any contract to purchase or subscribe for any securities in the Company or any member of the SMA Group or commitment whatsoever.

All information contained herein has been carefully prepared. Nevertheless, we do not guarantee its accuracy or completeness and nothing herein shall be construed to be a representation of such guarantee. The Company shall assume no liability for errors contained in this document, unless damages are caused intentionally or through gross negligence by the Company. Furthermore, the Company shall assume no liability for effects of activities that evolve from the basis of data and information provided by this presentation.


The information contained in this presentation is subject to amendment, revision and updating, which does not underlie any prior announcement by the Company. Certain statements contained in this presentation may be statements of future expectations and other forward-looking statements that are based on the management's current views and assumptions and involve known and unknown risks and uncertainties. Actual results, performance or events may differ materially from those in such statements as a result of, among others, factors, changing business or other market conditions and the prospects for growth anticipated by the management of the Company. These and other factors could adversely affect the outcome and financial effects of the plans and events described herein. The Company does not undertake any obligation to update or revise any forward-looking statements, whether as a result of new information, future events or otherwise. You should not place undue reliance on forward-looking statements which speak only as of the date of this presentation.

This presentation is for information purposes only and may not be further distributed or passed on to any party which is not the addressee of this presentation solely after prior consent of the Company. No part of this presentation must be copied, reproduced or cited by the addressees hereof other than for the purpose for which it has been provided to the addressee. The content of this presentation, meaning all texts, pictures and sounds, are protected by copyright. The contained information of the presentation is property of the Company.


This document is not an offer of securities for sale in the United States of America. Securities may not be offered or sold in the United States of America absent registration or an exemption from registration under the U.S. Securities Act of 1933 as amended.

SMA Solar Technologies AG


Key Figures



35+
Years




3,000
Employees



95+
GW



190
countries



1,200
Patents

Key Financials

	Sales	EBITDA	Inverter Capacity
2019 (Actual)	€915 million	€34 million	11.4 GW
2020 (Guidance)	€1.0 – 1.1 billion	€50 – 80 million	7.1 GW (H1 2020)

SMA Solar Technologies AG

Product Portfolio




USE CASES	HOME				
	Generate solar power	Store solar power	Manage energy	Refuel with solar power	Be your own grid
HARDWARE	<p>TS4-R MODULTECHNIK</p>				
	<p>SUNNY BOY 1.5/2.0/2.5</p>	<p>SUNNY BOY STORAGE 2.5</p>			
	<p>SUNNY BOY 3.0/3.6/4.0/5.0/6.0</p>	<p>SUNNY BOY STORAGE 3.7/5.0/6.0</p>	<p>SUNNY HOME MANAGER 2.0</p>	<p>SMA EV CHARGER</p>	<p>SUNNY ISLAND 4.4M/6.0H/8.0H</p>
	<p>SUNNY TRIPOWER 3.0/4.0/5.0/6.0</p>		<p>ENERGY METER</p>		
	<p>SUNNY TRIPOWER 8.0/10.0</p>	<p>SUNNY ISLAND 4.4M/6.0H/8.0H</p>			

USE CASES	BUSINESS			
	Generate solar power	Store solar power	Manage energy	Be your own grid
HARDWARE	<p>SUNNY TRIPOWER 1.5/20/25000TL (1.5/20/25kW)</p>	<p>SUNNY TRIPOWER CORE1 (50kW)</p>	<p>SUNNY TRIPOWER STORAGE 60</p>	<p>SMA DATA MANAGER M</p>
	<p>SMA STORAGE BUSINESS (76kWh)</p>		<p>ENERGY METER</p>	<p>SUNNY ISLAND 4.4M/6.0H/8.0H</p>
SOFTWARE	<p>SUNNY DESIGN powered by smart2</p> <p>SUNNY PORTAL powered by smart2</p> <p>SMA 360° APP</p> <p>SMA ENERGY APP</p>			
SERVICES	<p>Smart Connected</p> <p>Commissioning Support</p> <p>Extended Warranty</p> <p>Operation & Maintenance</p> <p>Repowering</p> <p>Solar Academy Training</p> <p>SMA SPOT More Solar Power on Trade</p>			


USE CASES	LARGE SCALE		
	Generate solar power	Store power	Manage energy
HARDWARE	<p>SUNNY HIGHPOWER PEAK3 (100kW/1000V + 150kW/1500V)</p>	<p>SUNNY CENTRAL (1850 - 4600 kW)</p>	<p>SMA DC/DC CONVERTER</p>
	<p>SUNNY CENTRAL STORAGE UP (2200 - 4600kW)</p>		<p>SMA DATA MANAGER L</p>
	<p>MEDIUM VOLTAGE POWER STATION</p>	<p>MEDIUM VOLTAGE POWER STATION</p>	<p>HYBRID CONTROLLER</p>
			<p>POWER PLANT MANAGER</p>

Inverter Compatibility with Ultra High-Power Modules

Topics for Today



Fundamentals behind ultra high-power modules and their electrical characteristics (Mainly I_{sc} / I_{mp})




Implications of higher power modules on inverter/module interface



Compatibility of high current modules with SMA inverters


Solar Cell Basics

From Silicon to Wafers




Solar Cell Basics

From M0 to M12 Wafers





Solar Cell Basics

From M0 to M12 Wafers



Solar Cell Basics


From M0 to M12 Wafers | implications of bigger cells?




$$I \propto I_L \propto \text{Irradiance} \propto \text{Cell Area}$$
$$V \propto V_D \propto \text{Temperature}$$

Solar Cell Basics

From M0 to M12 Wafers | Module Level



SMA Solar Technology



$$I \propto I_L \propto \text{Irradiance} \propto \text{Cell Area}$$


$$V \propto V_D \propto \text{Temperature}$$

Solar Cell Basics

From M0 to M12 Wafers | What about bifacial?




Bifacial module




=

Monofacial module




Solar Cell Basics

From M0 to M12 Wafers




PV inverter Basics

How does cell size affect down-stream system components?




$I_{\text{max power}}$

$I_{\text{short circuit}}$



Single MPPT Inverter





Multi-MPPT Inverter

$I_{\text{operating}}$


$I_{\text{short circuit DC}}$

PV inverter Basics

Inverter DC Short Circuit Current 1




Sum of short circuit current of all strings connected to an MPPT \leq short circuit current of MPPT **at worst case** temperature / irradiance combination




PV inverter Basics

Inverter DC Short Circuit Current 2




Max T
Max W/m²

Sum of short circuit current of all strings connected to an MPPT \leq short circuit current of MPPT **at worst case** temperature / irradiance combination




PV inverter Basics


Inverter Operating Current 1



Max operating current 1



Operating Current is controlled by the MPP Tracking by varying the load as seen by the string from 0 (short circuit) to infinity (open circuit) - i.e. "controlling" DC Voltage.



PV inverter Basics


Inverter Operating Current 2



Operating current shouldn't necessarily match to I_{mp} current of your string/array. Unlike short-circuit current this is generally a stochastic rather than a worst-case scenario sizing exercise.

Factors to consider:

- LID
- Soiling
- Airmass
- Irradiation (Azimuth/Tilt)
- Shadowing



1st year field data from two plants in Jordan to show distribution of I_{mp} across the year in comparison to STC I_{mp} current

Are inverters ready for high current modules?


SMA Inverters | Single-MPPT / Fused



Conditions: 0°C/70°C | 1,000W/m² | 20% rearside Irradiance

Inverter Model	Rated Capacity (kVA)	MPPT	Theoretical DC/AC Ratio Monofacial (550Wp)	Theoretical DC/AC Ratio Bifacial (600Wp)
SHP100-20 (1,000V)	100	1	2.24	2.40
SHP150-20 (1,500V)	150	1	2.30	2.26

- Larger Size Fuses must be used in combiner boxes depending on temperature profile
- Larger currents create better opportunity for combiner box type inverter due to 1 larger cable rather than multiple ones.
- Decentral Architecture Enables compensation of DC losses by oversizing whilst minimizing AC losses.
- Mismatch losses negligible (V_{mp} function of temperature)



Are inverters ready for high current modules?


SMA Inverters | Multi-MPPT / Fuseless



Conditions: 0°C/70°C | 1,000W/m² | 20% rearside Irradiance

Inverter Model (1,000V)	Rated Capacity (kVA)	MPPT	Theoretical DC/AC Ratio Monofacial (550Wp)	Theoretical DC/AC Ratio Bifacial (600Wp)
STP8.0-3AV-40	8	1 ⁽¹⁾	3.3	2
STP10.0-3AV-40	10	1 ⁽¹⁾	2.6	1.6
STP15000TL30	15	2	3.5	4.3
STP20000TL30	20	2	2.6	3.2
STP25000TL30	25	2	2.1	2.6
STP50-40	50	6	1.6	1.9
STP110-60	110	12	1.5	1.8

⁽¹⁾ Use of parallel MPPT operation is required.




● MPPT Short Circuit × MPPT Operating

Are inverters ready for high current modules?

General hints for multi-mppt inverters 1



- 1) String vs. MPPT ratings
- 2) Power Limitation per MPPT
- 3) Voltage dependent current ratings



Are inverters ready for high current modules?

General hints for multi-mppt inverters 2



Excerpt From PVsyst Documentation:

"By default, PVsyst assumes **that an inverter with 2 MPPT inputs behaves as 2 identical inverters of half the power.** That is, each MPPT input will have a "nominal power" of half the power of the full inverter.

If you check the option "Use Multi-MPPT feature", each MPPT input will be considered as an individual inverter with fixed $PNom(MPPT) = PNom(Inv) / NbMppt$.

Be careful: as in the PVsyst inverter database, there is no information about the maximum power (or current) for each individual MPPT input, **it is your responsibility to check in the data sheets whether the allocated power is compatible with the manufacturer's specifications."**

Thank you!



SMA Solar Technology AG

Sonnenallee 1
34266 Niestetal, Germany

Tel. +49 561 9522 0
Fax +49 561 9522 100

www.SMA.de
info@SMA.de

