

CSP Reference Power Plant

ata insights

Christian Schuhbauer
PPPDN
28.10.2020

Gefördert durch:



Bundesministerium
für Wirtschaft
und Energie

aufgrund eines Beschlusses
des Deutschen Bundestages

Agenda

1 Overall Design of CSP RP

2 Operating States of Receiver


3 Design of Subsystems

3.1 Receiver

3.2 Storage System

3.3 Steam Generator

3.4 Power Block




Overall Design

Layout

- **Minimized heat losses**
 - Compact arrangement of salt tanks and steam generator system
 - Turbines and ACCs are arranged close to each to minimize heat losses
- **Two steam generator units feed one turbine**
- **Lower placed drainage tank for draining exchanger units**

Layout for 2 x 200 MWeI









Operating States

Receiver


Five states for operation

- During a long-term shut down, **the solar tower including the heliostats is shut down.**
- To collect solar energy at first the salt circuit must be preheated and **filled** while some heliostats have to change position and **preheat the receiver.**
- After both parts are in standby mode,** the receiver is prepared for starting. Salt flows through absorber tubes and **solar operation can start.**




Receiver and Heat Transfer Cycle

Basic engineering – Design of main components



Panel data

Mean flow velocity	3.4 m/s
Irradiated absorber length	23 m
Width of panel	7.2 m



Receiver data

Heat Duty	700 MWth
Mean heat flux density	536 kW/m ²
Height/Diameter ratio	1.21
Number of serial panels	4
Estimated pressure loss (only absorber tubes)	6.5 bar
Minimum part load	19%

Receiver

Rating after parameter study

Optimization of Receiver Design

Investigation of 11 variants


Reduction of LCOH due to:

Longer lifetime by lowering max. heat flux density (850 kW/m²)

Lower investment costs due to:

- Austenitic stainless steel
- Small receiver (less irradiated tubes)
- Less welding seams
- Very low pressure drop

→ Solar field and receiver are perfectly matched to minimize the LCOH



Storage system

Tank & Insulation

Storage tanks:

Reference plant includes 50.000 t salt (6032 MWh)

Cold tank: Ø 42,9 m x 20 m

Hot tank: 2 x Ø 31,9 m x 20 m

Insulation:

Specific costs: 1000 €/m³ (cold tank) and 1100 €/m³ (hot tank)


Insulation thickness: Cold tank 350 mm; Hot tank 500 mm

Solar salt:

Material costs: 850 €/to

Melting costs: 150 €/to

Price indication of three different suppliers



Overall costs incl. markup for storage system will be in a range between 20 and 22 €/kWh_{th}

Steam Generator

Natural Circulation

Heat exchangers:

Power of one SG unit: $240 \text{ MW}_{\text{th}} \rightarrow 100 \text{ MW}_{\text{el}}$


\rightarrow 2 trains necessary for $200 \text{ MW}_{\text{el}}$

Rating of chosen design

+ Low pressure losses
(Evaporator: 6 bar, Reheater: 3 bar)

+ Low costs

- Lower load changes transients than once-through SG



Power Block

Boundary conditions and assumptions

Nominal power: 200 MWeI (2 x 200 MWeI)

Live steam parameters: 140 bar a / 550 °C

Air cooled condenser (ACC)

Design exhaust pressure: 135 mbar

Minimal pressure: 100 mbar

Air inlet temperature: 30°C; air humidity: 60 %
(night operation)

Nominal power consumption 6200 kW

Steam Turbine

Net efficiency 41,6% at 200 MW nominal load

Low efficiency drop (41,6% → 39,2%) at partial load
down to 50%

→ Reduced power consumption of ACC by speed control



Thank you very much!

Christian Schuhbauer
Head of New Business, PPPDN
christian.schuhbauer@man-es.com
+49 991 381 334
28th October, 2020

All data provided in this document is non-binding.

This data serves informational purposes only and is especially not guaranteed in any way.

Depending on the subsequent specific individual projects, the relevant data may be subject to changes and will be assessed and determined individually for each project. This will depend on the particular characteristics of each individual project, especially specific site and operational conditions.